

**ROAD DISC BRAKE**

Modell	model	SQUAD RACE 4.2 (disc brake)
Design	design	<b>MATT WHITE</b>
Carbonfaser	carbon fiber	<b>3K-Carbon</b>
Abmaße Felge	dimension rim	<b>622x18C tubeless ready</b>
Reifendimension	tyres	<b>clincher 23-40mm</b>
Reifendruck (max.)	tyre inflation pressure	<b>8,8 bar (23-622) /127 psi in (23-622) 7,5 bar (25-622) /108 psi in (25-622) 7,0 bar (26-622) /101 psi in (26-622) 6,0 bar (28-622) /87 psi in (28-622) 5,0 bar (30-622) / 72 psi in (30-622) 4,5 bar (33-622) / 65 psi in (33-622) 3,5 bar (40-622) / 50 psi in (40-622)</b>
Bremsfläche	brake surface	<b>none</b>
Bremsbeläge	brake pads	<b>none</b>
Gesamtgewicht [g]	total weight [g]	<b>1632</b>
max. empfohlenes Fahrergewicht inkl. Ausrüstung [kg]	max. recommended rider weight incl. Equipment [kg]	<b>110</b>
Zubehör	accessories	<b>XeNTiS warranty card XeNTiS rim tape</b>

Vorderrad	front wheel	
Felgenhöhe [mm]	rim depth [mm]	<b>42-ASYMMETRIC PROFILE</b>
Felgenbreite [mm]	rim width [mm]	<b>26</b>
Tachomagnet	speedometer magnet	<b>✓</b>
Vorderrad Nabe	front hub	<b>DT SWISS 350, 12-100mm, Center Lock®</b>
Einbaubreite Nabe [mm]	built in width hub [mm]	<b>100</b>
Speichenanzahl	spokes count	<b>28</b>
Speichen	spoke	<b>Sapim CX-Ray SP</b>
Speichennippel System	spoke-nipple system	<b>DT Squorx</b>
Speichenlänge [mm]	spoke lenght [mm]	<b>281</b>
Dekor	decor	<b>white</b>
Oberfläche (UV Schutz)	surface (UV protection)	<b>matt</b>
empfohlene Ventillänge [mm]	recommended valve length [mm]	<b>50</b>
Gewicht Schnellspanner Vorderrad [g]	weight quick release front wheel [g]	<b>-</b>

Hinterrad	rear wheel	
Felgenhöhe [mm]	rim depth [mm]	<b>42-ASYMMETRIC PROFILE</b>
Felgenbreite [mm]	rim width [mm]	<b>26</b>
Tachomagnet	speedometer magnet	<b>✓</b>
Hinterrad Nabe	rear hub	<b>DT SWISS 350, X12-142mm, Center Lock®</b>
Kompatibilität 1	compatibility 1	<b>Campagnolo 11/12-Speed</b>
Kompatibilität 2	compatibility 2	<b>Shimano / SRAM 10/11-Speed</b>
Kompatibilität 3	compatibility 3	<b>SRAM XDR 12-Speed</b>
Einbaubreite Nabe	built in width hub [mm]	<b>142</b>
Speichenanzahl	spokes count	<b>28</b>
Speichen	spoke	<b>Sapim CX-Ray SP</b>
Speichennippel System	spoke-nipple system	<b>DT Squorx</b>
Speichenlänge rechts [mm]	spoke lenght right [mm]	<b>281</b>
Speichenlänge links [mm]	spoke lenght left [mm]	<b>281</b>
Dekor	decor	<b>white</b>
Oberfläche (UV Schutz)	surface (UV protection)	<b>matt</b>
empfohlene Ventillänge [mm]	recommended valve length [mm]	<b>50</b>
Gewicht Schnellspanner Hinterrad [g]	weight quick release rear wheel [g]	<b>-</b>

Item Number		Description
<b>18SC42D410-S</b>	<b>1pair</b>	<b>Wheelset, SRAM/Shimano 10/11s</b>
<b>18XC42D410-S</b>	<b>1pair</b>	<b>Wheelset, SRAM XDR 12s</b>
<b>18CC42D410-S</b>	<b>1pair</b>	<b>Wheelset, Campagnolo 10/11/12s</b>
18SC42D410-R	1pcs	Rear wheel, SRAM/Shimano 10/11s
18XC42D410-R	1pcs	Rear wheel, SRAM XDR 12s
18CC42D410-R	1pcs	Rear wheel, Campagnolo 10/11/12s
18SC42D410-F	1pcs	Front wheel

XeNTiS Produkte können Abweichungen enthalten, Spezifikationen können ohne vorherige Ankündigungen geändert werden.  
Gewichtsschwankungen (+/- 5%) können aufgrund der Produktionsmethode des Laufrades auftreten. Irrtümer und Änderungen vorbehalten!

XeNTiS products may not be exactly as shown, specifications subject to change without notice.  
Weight tolerances (+/- 5%) may occur due to the manufacturing process. Errors and omissions excepted!