

ROAD DISC BRAKE

Modell	model	SQUAD SL 4.2 (disc brake)
Design	design	MATT WHITE
Carbonfaser	carbon fiber	UD-Carbon
Abmaße Felge	dimension rim	622x18C tubeless ready
Reifendimension	tyres	clincher 23-40mm
Reifendruck (max.)	tyre inflation pressure	8,8 bar (23-622) /127 psi in (23-622) 7,5 bar (25-622) /108 psi in (25-622) 7,0 bar (26-622) /101 psi in (26-622) 6,0 bar (28-622) /87 psi in (28-622) 5,0 bar (30-622) / 72 psi in (30-622) 4,5 bar (33-622) / 65 psi in (33-622) 3,5 bar (40-622) / 50 psi in (40-622)
Bremsfläche	brake surface	none
Bremsbeläge	brake pads	none
Gesamtgewicht [g]	total weight [g]	1299
max. empfohlenes Fahrergewicht inkl. Ausrüstung [kg]	max. recommended rider weight incl. Equipment [kg]	110
Zubehör	accessories	XeNTiS warranty card XeNTiS wheelbag XeNTiS rim tape

Vorderrad	front wheel	
Felgenhöhe [mm]	rim depth [mm]	42-ASYMMETRIC PROFILE
Felgenbreite [mm]	rim width [mm]	26
Tachomagnet	speedometer magnet	✓
Vorderrad Nabe	front hub	XeNTiS XH004, 12-100mm, Center Lock®
Einbaubreite Nabe [mm]	built in width hub [mm]	100
Speichenanzahl	spokes count	24
Speichen	spoke	Sapim CX-Ray SP
Speichennippel System	spoke-nipple system	DT Squorx
Speichenlänge [mm]	spoke lenght [mm]	269
Dekor	decor	white
Oberfläche (UV Schutz)	surface (UV protection)	matt
empfohlene Ventillänge [mm]	recommended valve length [mm]	50
Gewicht Schnellspanner Vorderrad [g]	weight quick release front wheel [g]	-

Hinterrad	rear wheel	
Felgenhöhe [mm]	rim depth [mm]	42-ASYMMETRIC PROFILE
Felgenbreite [mm]	rim width [mm]	26
Tachomagnet	speedometer magnet	✓
Hinterrad Nabe	rear hub	XeNTiS XH004, X12-142mm, Center Lock®
Kompatibilität 1	compatibility 1	Campagnolo 11/12-Speed
Kompatibilität 2	compatibility 2	Shimano / SRAM 10/11-Speed
Kompatibilität 3	compatibility 3	SRAM XDR 12-Speed
Einbaubreite Nabe	built in width hub [mm]	142
Speichenanzahl	spokes count	24
Speichen	spoke	Sapim CX-Ray SP
Speichennippel System	spoke-nipple system	DT Squorx
Speichenlänge rechts [mm]	spoke lenght right [mm]	278
Speichenlänge links [mm]	spoke lenght left [mm]	278
Dekor	decor	white
Oberfläche (UV Schutz)	surface (UV protection)	matt
empfohlene Ventillänge [mm]	recommended valve length [mm]	50
Gewicht Schnellspanner Hinterrad [g]	weight quick release rear wheel [g]	-

Item Number		Description
19SC42DS400-S	1pair	Wheelset, SRAM/Shimano 10/11s
19XC42DS400-S	1pair	Wheelset, SRAM XDR 12s
19CC42DS400-S	1pair	Wheelset, Campagnolo 10/11/12s
19SC42DS400-R	1pcs	Rear wheel, SRAM/Shimano 10/11s
19XC42DS400-R	1pcs	Rear wheel, SRAM XDR 12s
19CC42DS400-R	1pcs	Rear wheel, Campagnolo 10/11/12s
19SC42DS400-F	1pcs	Front wheel

XeNTiS Produkte können Abweichungen enthalten, Spezifikationen können ohne vorherige Ankündigungen geändert werden.
Gewichtsschwankungen (+/- 5%) können aufgrund der Produktionsmethode des Laufrades auftreten. Irrtümer und Änderungen vorbehalten!

XeNTiS products may not be exactly as shown, specifications subject to change without notice.
Weight tolerances (+/- 5%) may occur due to the manufacturing process. Errors and omissions excepted!